



## General Product Specifications

<u>Description</u>	<u>Minimum</u>	<u>Maximum</u>
Single Panel Width (Regular)	6"	42" for 3.5"&4.5" louvers, 36" for other louver type
Single Panel Width (Bifold)	6"	26"
Single Panel Height	10"	133"
Shutter Width (Without T Post)	N/A	4x single panel width (bifold) + frame
Shutter Width (With T Post)	N/A	Unlimited <b>(For orders shipped by sea, frames longer than 142" will be spliced in the middle. For orders shipped by air, frames longer than 120" will be spliced in the middle.)</b>
Shutter Height	N/A	133" + frame

\* For frame and stile exceeding 108", there will be a visible finger joint line in the middle.

### Shutters without bottom supports

Normandy shutters will be covered by our warranty for this application, subject to our standard specification limitations and the guidelines listed below:

#### All Normandy panel configurations:

- ◇ You must inform Norman Shutters of situations where shutters will not have bottom support when placing the initial order, or warranty will be considered void.
- ◇ Informing Norman Shutters when placing such orders ensures that the factory will add extra hinges to support the panel. This will reduce the probability of the panels sagging and increase shutter integrity.
- ◇ If you fail to notify Norman Shutters that the shutter will be used without a bottom support or used as doors, this will constitute a misapplication of the shutter. Consequently, you will be responsible for the cost of any RGA Reorder that is submitted.
- ◇ If you want a bifold shutter, a track must be ordered to support the panels.