

NORMAN® Perfect Tilt® RF

SHUTTER MOTORIZATION TECHNOLOGY THAT'S **REALLY FANTASTIC**



Introducing PerfectTilt® RF, Norman®'s revolutionary remote controlled tilting system that requires no plug-in A/C adapter or hardwiring. Using control technologies found in high-end stereo equipment, the PerfectTilt® RF signal has a range of up to 65 ft.

BENEFITS

- Norman® is the only national brand that offers motorization on shutters
- Perfect for hard to reach windows such as skylights and tall windows
- No need to plug-in, no cords, no hardwiring
- Tilt multiple panels in sync or individually
- Includes InvisibleTilt™ system, a completely tilt-rod-free solution for a more streamlined view and improved energy efficiency
- Larger solar panels on solar modules absorb more energy than ever before
- Ergonomic remote includes preset options and can control unlimited number of shutters in range
- Utilizes RF signal, not traditional infrared: for precise reception, range up to 65 ft., no sensor holes, and no need to point remote directly at receiver
- Set up the included e-timer from a computer or smartphone from anywhere at anytime with our proprietary web interface! Tilt your shutters automatically on whichever day or time you choose! (available March, 2013)
- Whisper quiet, gear-driven system
- PerfectTilt® RF wires are concealed inside panel, completely hidden from view
- Extra battery packs can be installed as add-on for longer periods between recharges

NORMAN®. PUSHING TECHNOLOGY FURTHER TO REDEFINE EXPECTATIONS. EVERYDAY.

Perfect Tilt® RF



- Innovative e-timer included
- 8 preset angles
- RF signal with range up to 65 ft.

CHOOSE FROM 2 POWER OPTIONS

- **SOLAR MODULE:** Let in the sunlight with the power of the sun itself. PerfectTilt® RF Solar is the most innovative and **Green** solution for even the most challenging situations.
- **RECHARGEABLE BATTERY MODULE:** High-end motor optimized for rechargeable batteries delivers smooth and consistent performance for windows at any width or height.

PerfectTilt® RF Specifications	
Program	Available in Woodlore®, Woodlore Plus™, Brightwood™, Normandy® and Sussex® Shutters
Specialty Shutter Shapes	All shapes except shapes without a vertical stile in the middle (for example, eyebrow)
Tilting System	Available in InvisibleTilt™ only
Louver Sizes	Elliptical louvers in 2.5" , 3.5" or 4.5" only
Panel Sizes	Min. Panel Height: 18"
	Max. Panel Height without divider rail: 78" for Normandy®, Sussex®, Brightwood™ and Woodlore Plus™; 74" for Woodlore®
	Panel Width Limit: same as regular shutters
Channels for Remote Control	Up to 5 channels (20 motors for each channel)
Remote Control	2 × AAA
Motor Battery	6 × AA
Warranty	Module unit and remote control unit have 2 year warranty under normal operation
Price	Contact your sales manager